

# BTX-SUPREME

## B05536

### DESCRIPTION

An extremely bright hybrid moving head (BEAM, SPOT, WASH) for big clubs, concert stages and rental

### FEATURES

- BTX-SUPREME HYBRID is an extremely bright hybrid moving head for big clubs, concert stages and rental!
- The OSRAM SIRIUS HRI 471W SN lamp (CCT: 7500K), combined with Hi-Q optics, make it incredibly bright:
  - BEAM: 1,8° ~ 22°, max. 485'000 lux @ 10m
  - SPOT: 3° ~ 42°, max. 132'000 lux @ 10m
- The different effect wheels and filters create dazzling effects:
  - Precise and fast CMY-color mixing
  - 1 color wheel with 13 carefully selected colors, including 3200K CTO-filter + white
  - 1 gobo wheel with 13 static gobos + open
  - 1 gobo wheel with 9 easily replaceable rotating/indexable glass gobos (OD: 17mm / IM: 12mm)
  - 2 Prism wheels, each with 4 rotating/indexable prisms, can be combined to create stunning effects!
  - 1 Rotating/indexable animation wheel that can be combined with different gobos
  - 1 light FROST-effect 0-100%
  - 1 heavy FROST-effect 0-100%
  - 1 Hi-CRI filter to improve the white light quality
- Motorized ZOOM + FOCUS with calibrated DMX-values
- Accurate Dimmer/shutter for linear dimming and variable strobe effects
- The 3-Phase stepper motors assure very fast 540°/270° PAN/TILT movements with 8 or 16bit precision.
- Selectable PAN range: 540° or 630°
- Modular setup for easy servicing and cleaning.
- Supported protocols: DMX512/RDM, Art-Net™, sACN
- Integrated wireless DMX module (W-DMX Sweden) with internal antenna to prevent antenna breakage.
- 2 DMX channel modes (standard: 24ch & Extended: 35ch) for maximum flexibility
- 2.8" Color touch screen with automatic display rotation for easy and intuitive menu navigation
- Rotary encoder for easy scrolling through the intuitive setup menu
- Factory & user defaults: easily save and recall your own preferred settings!
- Easy firmware updates via USB memory stick to keep your machine always up-to-date
- Remote lamp on/off control
- Remote FULL 471W / ECO 360W lamp control to extend the lifetime, up to 2'000 hours.
- Neutrik® 3pin & 5pin XLR & RJ45 network in/outputs for maximum flexibility in a professional environment
- Neutrik® PowerCON TRUE1in/outputs: up to 12A can be daisy chained for easy installation
- Equipped with 2 omega brackets for fast installation.
- Power consumption: max. 800W






[www.briteq-lighting.com](http://www.briteq-lighting.com) | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2021 by BEGLEC NV. All rights reserved.



## TECHNICAL SPECIFICATIONS

<b>General : Application</b>	DJ & Club, Stage & Rental
<b>General : Series</b>	No
<b>General : Dimensions (cm)</b>	54.5 x 39.7 x 47
<b>General : Weight (kg)</b>	26.5
<b>General : Powerinput</b>	AC 100 - 240V, 50/60Hz
<b>General : Energy Label</b>	No
<b>General : Power consumption W</b>	800
<b>General : Color</b>	black
<b>General : Display</b>	touchscreen
<b>General : Fixation</b>	included omega bracket
<b>General : IP rating</b>	indoor
<b>Control : Modes</b>	standalone, manual
<b>Control : manual</b>	Yes
<b>Control : Master/Slave</b>	No
<b>Control : SMART-DMX</b>	No
<b>Control : Standalone</b>	fixed
<b>Control : programmable</b>	Yes
<b>Control : upgradable software</b>	Yes
<b>Control : maximum DMX channels</b>	35
<b>Light : lamp socket</b>	none
<b>Light : Lux</b>	1'950'600 @5m (beam 1.8°)
<b>Light : lamp</b>	Discharge
<b>Light : min. color temperature (K)</b>	3200
<b>Light : max. color temperature (K)</b>	7500
<b>Light : CRI</b>	90
<b>Light : mix colors</b>	Yes
<b>Light : functions</b>	motorized focus, motorized zoom, iris
<b>Light : fixed gobos</b>	13
<b>Light : rotating gobos</b>	9
<b>Light : min. beam angle (°)</b>	1.8
<b>Light : max. beam angle (°)</b>	42
<b>Light : min. refresh rate (kHz)</b>	No
<b>Light : max. refresh rate (kHz)</b>	No
<b>Connections : input</b>	3 pin XLR, 5 pin XLR, artnet, RJ45, rdm, wireless DMX
<b>Connections : output</b>	3 pin XLR, 5 pin XLR, PowerCon® TRUE1, artnet, RJ45, rdm, wireless DMX
<b>Brand</b>	BRITEQ
<b>EANCode</b>	5420025655361



[www.briteq-lighting.com](http://www.briteq-lighting.com) | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2021 by BEGLEC NV. All rights reserved.