

BT-NODE24 (5PIN XLR)

05015

DESCRIPTION

High speed Art-Net & sACN Node with 4 highly configurable DMX ports (XLR 5-pin) with web interface and compatible with DHCP, RDM, NFC and Gigabit Ethernet with PoE.

FEATURES

- High speed Art-Net and sACN Node with 4 highly configurable DMX ports.
- Gigabit Ethernet I/O based on high speed Marvell switch, without linking delay.
- Automatic Ethernet bypass on power fails.
- Perfect for install market with configurations over Art-Net support and DHCP.
- Complies to IEEE 802.3-2005 standard for fully compliant hi-speed Gigabit Ethernet over long cable lengths.
- Integrated web interface with support for mobile devices.
- NFC tag for easy website access on mobile devices.
- The 4 DMX ports can all be configured as in or outputs:
 - Configured as input: normal mode
 - Configured as output: single, LTP, HTP or ZERO mode.
- Multiple pre-defined presets available and custom presets.
- RDM over Art-Net compatible.
- All DMX ports are equipped with 3pin or 5pin Neutrik® XLR-connectors (both versions available)
- 100% electrical isolation between all in/outputs: problems on 1 port will not influence the other ports.
- MIDI bridge functionality via Ethernet coming soon.
- Power options:
 - 100-240VAC 50/60Hz Neutrik® TRUE-1 daisy chaining.
 - PoE class 0 input. From 36V to 57V
- Housing ½ 19" diecast housing with different installation options:
 - 1-unit fits 1U 19" rack (19" adapter included)
 - 2-units fit together in a 1U 19" rack (adapters included)
 - Easy truss mounting with wall adapter (optional)
 - Strong rubber protection adapters for stage use (optional)
- Developed by Briteq® in Belgium and made in Europe!



www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2019 by BEGLEC NV. All rights reserved.



TECHNICAL SPECIFICATIONS

General : Application	Architectural, Stage & Rental
General : Dimensions (cm)	22.2 x 44 x 20.5
General : Weight (kg)	1.25
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	7
General : Color	black
General : Display	none
General : Fixation	19" rack mountable
General : RU	1U
General : IP rating	indoor
Control : programmable	No
Control : upgradable software	Yes
Control : maximum DMX channels	2048
Connections : input	5 pin XLR, TRUE1 powerCON, midi, usb, artnet, rdm
Connections : output	5 pin XLR, TRUE1 powerCON, midi, usb, artnet, rdm
Brand	BRITEQ
EA NCode	5420025650151
Discontinued	No



YOUR DEALER



www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2019 by BEGLEC NV. All rights reserved.