

BT-TVPANEL TW

B06032

DESCRIPTION

Professional soft-light with tunable white and possible battery power for TV studio and (dry) outdoor applications

FEATURES

- Professional soft-light for TV-studio and outdoor applications (only under dry conditions).
- Compact but powerful output: 640 CW / WW LEDs with 260W total power.
- Tunable white 3000K → 5600K with precise CCT-presets.
- Excellent photometric specifications: Ra > 98, TLCI > 99, ...
- Intelligently designed Aluminum finish for multifunctional use:
 - **PHOTO & TV-STUDIO:** "click-on" external 100V - 240V Power supply with V-LOCK
 - **TV, FILM, REPORTER, ...** : By using 1 or 2 optional standard V-LOCK batteries (14.8V and 26V compatible)
- Easily exchangeable frost filters + possibility to add extra (color) filter sheets.
- Different optional accessories: 8 leaf barndoor, manual yoke, intensifier, softbox, , ...
- Beam angle 115°
- Excellent dimmer electronics with 4 dimmer curves, dimmer speed control.
- Flicker free dimming down to 0% with refresh rates between 900Hz and 25kHz.
- Four dimmer curves: linear, square, inverse square, S-curve.
- Easy stand-alone use: 3 rotary knobs for dimming, CCT-presets & seamless CCT-adjustment.
- Full DMX control with different modes and control channel.
- Wireless DMX (optional WTR dongle) or cabled XLR 3pin / 5pin in/outputs.
- RDM-functionality for remote setting and monitoring.
- Very low-noise temperature-controlled fan cooling.
- Lock function to avoid unwanted altering of the settings.
- Default Factory Reset + user settings can be saved/loaded.
- 2x 16character OLED display with touch buttons for easy setup.
- Optional manual studio yoke is available.
- High lumen output: 19'000 lm
- PowerCON TRUE1 compatible in/outputs for easy daisy chaining.
- The included 28mm TV spigot is used to easily hang the projector (possibly in combination with the optional "TV-SPIGOT RECEIVER").






www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2022 by BEGLEC NV. All rights reserved.

TECHNICAL SPECIFICATIONS

General : Dimensions (cm)	56.2 x 36.8 x 19.5
General : Weight (kg)	9.7
General : Powerinput	AC 100 - 240V, 50/60Hz, Battery
General : Works on battery	yes
General : Energy Label	No
General : Power consumption W	290
General : Color	black
General : Display	OLED
General : Fixation	optional omega bracket
General : IP rating	indoor
Control : Modes	standalone fixed, manual, DMX
Control : Protocol	DMX, Wireless DMX, RDM
Control : programmable	No
Control : upgradable software	Yes
Control : maximum DMX channels	7
Light : lamp socket	No
Light : Lux	401 @5m (beam 115°)
Light : lamp	LED
Light : min. color temperature (K)	3000
Light : max. color temperature (K)	5600
Light : CRI	98
Light : colors	White, Cold white, Warm white
Light : mix colors	Yes
Light : functions	manual frost
Light : min. beam angle (°)	115
Light : max. beam angle (°)	115
Light : max. refresh rate (kHz)	25
Connections : input	3 pin XLR, 5 pin XLR, wireless DMX optional, usb, rdm, PowerCon® TRUE1 or compatible
Connections : output	3 pin XLR, 5 pin XLR, rdm, PowerCon® TRUE1 or compatible
Brand	BRITEQ
EANCode	5420025660327



www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2022 by BEGLEC NV. All rights reserved.