MFL –Tree Menu (v. 1.1)




TX LINK Menu
Status
ON/OFF
Mode
IFB / ANT
Filter
150-840 / 470-840 / BPF / EXTERN
BP filter center freq.
Central freq. 404÷788 MHz
(Bandwidth 25MHz)
Gain
With IFB Mode: -23.5 ÷ 8.0 dB
With ANT Mode & filter:
- BPF: -28.0 ÷ 3.5 dB
- EXTERN: -22.0 ÷ 9.5 dB
- 150-840: -20.0 ÷ 11.5 dB
- 470-840: -20.0 ÷ 11.5 dB
Booster
enabled / disabled
Booster supply
Failsafe
enabled / disabled
Ext filter att.
0.0 ÷ 6.0 dB
BP filter
ID
Serial
App FW ver
Center freq range
Filter bandwidth
Transmitter param
ID
Serial
Current limits
Optical power
Temperature
Offset gain
Wavelength
Life time
Only with ANT Mode
Only with ANT Mode & BPF filter.
BPF settable only with the option MFL-BF1


RX LINK Menu
Status
ON/OFF
Mode
IFB / ANT
Gain
-13.5 ÷ 18.0 dB
Failsafe
enabled / disabled
Optical power
Optical pwr. corr.
ON / OFF
Receiver param
ID
Serial
Opt rx pwr limits
Temperature
Offset gain
Wavelength
Life time