

MAGEWELL

Ultra Stream SDI Technical Specifications

Copyright (c) 2011–2019 [Magewell Electronics Co., Ltd.](#) All rights reserved.

Specifications are based on current hardware, firmware and software revisions, and are subject to change without notice.

Windows is trademark or registered trademark of Microsoft Corporation.

Android is trademark or registered trademark of Google Corporation.

iOS is trademark or registered trademark of Apple Corporation.

Revised 16/08/2019

Supported Mobile Clients

- Android
 - Android 5.0 and above
- iOS
 - iOS 9.0 and above
- iPhone
 - iPhone 5s
 - iPhone SE
 - iPhone 6 / iPhone 6s / iPhone 6 Plus / iPhone 6s Plus
 - iPhone 7 / iPhone 7 Plus
 - iPhone 8 / iPhone 8 Plus
 - iPhone X
- iPod Touch
 - iPod Touch 5
 - iPod Touch 6

Supported Web Browser

- Microsoft Internet Explorer 11
- Microsoft Edge
- Mozilla Firefox version 61 and above
- Google Chrome version 49 and above
- Apple Safari 11.1 and above
- Opera 55.0.2994.44 and above

Input Interfaces

- BNC
 - SD/HD/3G SDI
- 3.5mm audio jack
 - Microphone interface

Output Interfaces

- BNC
 - SD/HD/3G SDI
- USB
 - USB 2.0
- 3.5mm audio jack
 - Headphone interface

Network Interfaces

- Wired Ethernet
 - 10/100/1000Mbps Ethernet
- Wi-Fi
 - IEEE 802.11 a/b/g/n/ac

- USB
 - USB 3G/4G Modem (not included)

Bluetooth

- Bluetooth 4.0 BLE

SDI Specific Features

- Support for SD/HD/3Ga/3Gb/3Ga-DL/3Gb-DS standards
- Support for 2K (2048x1080) input and loopthrough signals
- Support for 8/10/12-bit color depths
- Support for 60p, 60i, 50p, 50i, 30p, 25p signal formats
- Limited support for the first stream of 3Gb-DS
- Limited support for the first link of dual link interfaces
 - YCbCr 4:2:2 10-bit 1080p 50/59.94/60: output as 1080i 50/59.94/60
 - YCbCr 4:4:4 10-bit: output as 4:2:2
 - RGB 4:4:4: R/B sub-sampled

Analog Audio Features

- Extraction of stereo embedded SDI audio for recording and output via 3.5mm stereo mini-jack Line Out
- Recording and streaming analog audio via 3.5 mm microphone interface

Streaming Features

- Support for live streaming using RTMP protocol to software including Flash Media Server, Wowza, Red5 and Nginx server
- Streaming to Facebook, Twitch and YouTube platforms
- Support for streaming to 2 servers simultaneously

Recording Features (to USB Flash Drive)

- Support for H.264/HEVC (video) and AAC High Quality (audio) encoding
- Supports recording at input signal resolution up to 2048x1080
- Support for 1920x1080, 1600x1200, 1440x1080, 1440x900, 1280x1024, 1280x960, 1280x800, 1280x720, 1200x900, 1024x768, 960x540, 800x600, 768x576, 720x576, 720x480, 640x480, 640x360, 480x360 resolutions
- Support for 60fps, 50fps, 30fps, 25fps, 24fps, 15fps frame rates
- Support for recording as MP4 files
- USB Flash Drive file system format: FAT32, NTFS, exFAT, VFAT

Recording Features (to Mobile Device)

- Support for recording at up to 1280x720, 30fps
- Support for recording as MP4 files
- Take still image snapshots during recording
- Save recording files and screenshots to system album
- Input signal previewing
- Timer recording: 15s, 30s, 1min, 2min, 5min

Remote Control Features in App

- Remotely control recording and streaming
- Remotely check device status by multiple users simultaneously
- Support for setting volume, network, recording and live streaming parameters
- Support for checking and safely updating device firmware (can also reset to factory firmware version)
- Simultaneous main stream and sub stream encoding with customizable parameters
- The bitrate for main stream is up to 8 Mbps while for sub stream is 1 Mbps
- Support for modifying output AAC bitrate
- In-app online help
- Support for multiple users log-in simultaneously
- Support for device configuration using Web UI

LED Indicator

- Indicates the state of the input signal, Ethernet Network, Wi-Fi, USB flash drive
- Indicates the working state of the device: startup, recording, streaming, update

Form Factor

- 94.20mm x 94.20mm x 22.30mm

Accessories

- AC adapter

Power Supply and Consumption

- Power port
 - 5V/2A
- Max power consumption: ~6.0 W

Working Environment

- Operating temperature: 0 to 40 deg C
- Storage temperature: -20 to 70 deg C
- Relative humidity: 5% to 90% non-condensing