



P5B-SA

Basic Protection Against Power Surges for Computers and Electronics

Includes: User Manual

Technical Specifications

Output

Number of Outlets	5.0
Receptacle Style	India/South Africa

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz
Input Connections	Indian/South African BS 546A
Cord Length	1.83meters
Number of Power Cords	1
Maximum Input Current	16.0A
Maximum Line Current	13A

Surge Protection and Filtering

Surge energy rating	960Joules
eP Joule Rating	1060
Peak Current Common Mode	13kAmps
Peak Current Normal Mode	13kAmps

Physical

Maximum Height	451MM, 45.09CM
Maximum Width	83MM, 8.26CM
Maximum Depth	45MM, 4.5CM
Net Weight	0.7KG
Shipping weight	0.74KG
Shipping Height	457MM, 45.72CM
Shipping Width	140MM, 13.97CM
Shipping Depth	64MM, 6.35CM

Color	Charcoal
Master Carton Dimensions (Length x Width x Height)	470 x 356 x 292MM
Master Carton Units	12.0
Units per Pallet	192.0
SCC Codes	1073130423873 4

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-15000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters

Conformance

Standard warranty	Lifetime
--------------------------	----------

Sustainable Offer Status

PEP	Available in Documentation tab
EOLI	Available in Documentation tab

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our Privacy Policy.

Sign up

WHO WE ARE

- [About APC](#)
- [Investor Relations](#)
- [Careers](#)
- [Sustainability](#)

CONNECT WITH US

- [Press](#)
- [APC Blog](#)
- [Schneider Electric Data Centre Blog](#)

FIND A RESELLER

Find

CATALOG KEYCODE

Go


[Terms & Conditions](#)

[Data Privacy and Cookie Policy](#)

2020, APC by Schneider Electric