BT-THEATRE 20WW (BLACK)

DESCRIPTION

Stylish compact 20watt warm white (3000K) LED theater spot with high CRIfactor (92) and amber drift effect

FEATURES

- Stylish compact LED theater spot with an extruded anodized aluminum housing.
- 20watt LED, warm white 3000K with amber drift effect (DIM TO WARM).
- High CRI-factor (92) for natural colors.
- NO DMX inside: can be dimmed using traditional TRIAC dimmers or with the dimmer knob on the back panel.
- Beam angle: 15°
- Thanks to the included 20° & 25° frost filters this attractive projector can be used for many different applications.
- Color frame for color filters and four-leaf barndoor included.
- Completely silent operation, no noisy cooling fans on board.
- Fixed mains power cord with standard mains plug (CEE 7/7) on the back panel.









www.briteq-lighting.com | https://www.facebook.com/Briteq

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2020 by BEGLEC NV. All rights reserved.

TECHNICAL SPECIFICATIONS

Architectural, Stage & Rental, **General: Application**

18.6 x 14.1 x 21.1 (without **General: Dimensions (cm)**

barndoor)

General: Weight (kg) 2.5 **General: Powerinput** AC 240V, 50Hz

General: Energy Label No **General: Power consumption W** 20 **General: Color** black **General: Display** No

General: Fixation optional standard clamp

General: IP rating indoor manual **Control: Modes Control: manual** Yes **Control: Master/Slave** No **Control: SMART-DMX** No **Control: Standalone** no **Control: programmable** No **Control: upgradable software** No **Light: lamp socket** none

Light: Lux 216 (@5m, beam 15°)

Light: lamp LED Light: min. color temperature (K) 1900 Light: max. color temperature (K) 3000 Light: CRI 92

Light: colors Amber, Warm white

Light: mix colors Light: functions manual frost

Light: min. beam angle (°) 15 **Light**: max. beam angle (°) 25 Light: min. refresh rate (kHz) No Light: max. refresh rate (kHz) No

Connections: input Schuko CEE 7/7 **Brand** BRITEQ 5420025660280 **EA NCode**

LUX (full on) 5401 1350 600 338 216 150 **BT-THEATRE 20WW** BEAM: 15° $\begin{array}{ccc} \text{DISTANCE (m)} & 1 \\ \text{BEAM } \varnothing \text{ (cm)} & 26 \end{array}$ 2 53 3 79 5 105 132 158









