

BEAMSPOT-4BAR NW

05508

DESCRIPTION

This compact 4bar has four 15W projectors with a very narrow 4° beam

FEATURES

- This compact 4bar has four 15W projectors with a very narrow 4° beam.
- Thanks to the included 10° & 45° filters this bar can also be used for exhibition booths, clubs, shops, ... (perfect to light up small objects and small tables)
- Natural white 4500K with high CRI-factor (>90).
- 4 different DMX-modes: control via 1, 2, 4 or 5 channels.
- RDM-functionality for easy remote setup: DMX addressing, channel mode, ...
- The OLED-display assures easy navigation in the different setup menus.
- TV-Studio ready: no cooling fans and flicker free 1200Hz LED refresh rate.
- Selectable dimming speed: from slow halogen lamp behavior to fast led behavior
- Four dimmer curves: linear, square, inverse square, S-curve
- In case of DMX failure you can choose between blackout and freeze mode.
- Lock function to avoid unwanted altering of the settings.
- Default factory settings + user settings can be saved/loaded.
- 3pin & 5pin DMX in/outputs and Neutrik® PowerCON® in/outputs for easy daisy chaining.



www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2018 by BEGLEC NV. All rights reserved.

SPECIFICATIONS

General : Application	DJ & Club, Stage & Rental
General : Dimensions (cm)	55.2 x 8.5 x 31.5
General : Weight (kg)	6.74
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	71
General : Color	black
General : Display	OLED
General : IP rating	indoor
Control : manual	Yes
Control : Master/Slave	Yes
Control : SMART-DMX	No
Control : Standalone	automatic, fixed
Control : Type included remote	Infra Red
Control : programmable	No
Control : upgradable software	Yes
Control : maximum DMX channels	5
Light : lamp socket	No
Light : lamp	LED
Light : min. color temperature (K)	4500
Light : CRI	90
Light : mix colors	No
Light : iris	No
Light : min. beam angle (°)	4
Light : max. beam angle (°)	45
Connections : input	3 pin XLR, 5 pin XLR, powercon
Connections : output	3 pin XLR, 5 pin XLR, powercon
Brand	BRITEQ
EANCode	5420025655088
Discontinued	No



www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2018 by BEGLEC NV. All rights reserved.