## AMP200.4

## DESCRIPTION

Professional 4-channel power amplifier in an extremely compact 19" 1U-housing

## **FEATURES**

- Professional 4-channel power amplifier in an extremely compact 19" 1U-housing (H: 44mm)
- > The unit houses 2 separate class-D amplifiers that can be configured independently to obtain the following combinations:
  - > Both amps in stereo mode: 4x 200Wrms @  $4\Omega$  (4x 100Wrms @  $8\Omega$ )
  - $\rightarrow$  Both amps in mono mode: 4x 200Wrms @ 4 $\Omega$  (4x 100Wrms @ 8 $\Omega$ )
  - $\rightarrow$  Both amps in Bridge mode: 2x 400Wrms @ 8 $\Omega$
  - > 3 Channel mode (2 sattelites + sub): 2x 200Wrms @  $4\Omega$  (or 2x 100Wrms @  $8\Omega$ ) + 1x 400Wrms @  $8\Omega$
- > 120Hz High Pass Filter on/off switch for satellite speakers
- > 120Hz Low Pass Filter on/off switch for subwoofer
- > DC fault + high temperature + overload and short circuit protections
- A plastic cover (included) can be installed to prevent access to the level knobs
- Balanced XLR inputs
- > Speakon® compatible outputs









## TECHNICAL SPECIFICATIONS

**General: Dimensions (cm)** 48.3 x 4.4 x 24 **General**: Weight (kg) 4.71 **General**: Color black

**General: Powerinput** AC 230V, 50Hz

**General**: Energy Label No **General**: Display No **General: RU** 1U **General: IP rating** indoor Audio: min. frequency (Hz) 20 Audio: max. frequency (Hz) 20000 **Audio:** frequency range 120 Audio: S/N ratio (> dB) 100 Audio: max. output channels Audio: Wrms  $4\Omega$  stereo, per 200 channel

Audio : Wrms  $8\Omega$  stereo, per

100 channel Audio: Wrms  $8\Omega$  bridge 400

**Audio: functions** fixed crossover **Connections: input** 3 pin XLR, IEC **Connections: output** speakon **Brand** JB SYSTEMS **EANCode** 5420025681315 SKU

B08131







