

Camera Mount Clamps for Proaim Alpha Stand (CT-CMCL-01)

Assembly Manual



What's In The Box

Please inspect the contents of your shipped package to ensure you have received everything that is listed below.



Camera Mount Clamps for Alpha Stand

All rights reserved.

No part of this document may be reproduced, stored in a retrieval system, or transmitted by any form or by any means, electronic, mechanical, photo-copying, recording, or otherwise, except as may be expressly permitted by the applicable copyright statutes or in writing by the Publisher.

Camera Mount Clamps Setup

- Open the Clamp by loosening its ratchet knob as shown in the image.



- Remove the bush from inside the Clamp.
Feature: Two mounting Clamps vertically attach to your rod and provide a mount for a separately available mounting rod and horseshoe camera mount, allowing you to form a camera mounting system.



- Mount the Clamp on the Alpha stand (Not Included).

NOTE: The Clamp can slide up/down and rotate 360° while securely clamped to the mast of your stand, ensuring a solid attachment with its locking knobs.



- After mounting the Clamp, secure it by tightening the ratchet knob.
- Repeat the same process with the second Clamp.

NOTE: Locking knob secures the stand in place, ensuring strength with a high level of safety.



- Pull and loosen the second ratchet knob of the Clamp and insert the rod (Not Included) in it.



- Insert rod in the second clamp.
NOTE: The Clamps incorporate 1/4"-20 and 3/8"-16 mounting threads for accessory mounting.



Effortless Movement Camera Mount Clamps Slides Up or Down



Camera Mount Clamps 360° Rotation



- After inserting the rod, properly secure it using the ratchet knob, as shown in the image.
- Pull and loosen the ratchet knob of the Horseshoe mount (**Not Included**).



- Slide the Horseshoe mount (**Not Included**) into the rod and tighten the ratchet knob to secure it.



- Mount the Mitchell plate mount (**Not Included**) on the Horseshoe mount by matching their threads and inserting bolts in the threads.



- After inserting the bolts, tighten the bolts using the Allen key to secure the Mitchell plate.
- Now, loosen and remove the castle ring of the fluid head (**Not Included**).



- After removing the Castle ring, mount the fluid head on the Mitchell plate.



- After mounting the Fluid head (**Not Included**), re-insert the castle ring from the bottom, as shown in the image.



- Properly tighten the Castle ring to completely secure the fluid head (**Not Included**).



- Press the knob of the Fluid head and remove the top plate.
- After removing the plate, attach it to the Camera (**Not Included**) by aligning their threads.



- After attaching the plate, tighten the screws using a screwdriver.
- Now, slide the Camera onto the fluid head.



- After mounting the Camera (**Not Included**), press the locking lever of the fluid head to secure it in its place, as shown in the image.



- The Camera is properly mounted.
- The setup is ready to use.



**YOUR PROAIM CAMERA MOUNT CLAMPS FOR PROAIM ALPHA STAND
ALL DRESSED UP AND READY TO GO!**



(SHOWN WITH OPTIONAL ACCESSORIES)

Warranty: We offer one year warranty for our products from date of purchase. Within this period of time, we will repair it without charge for labor or parts. Warranty doesn't cover transportation costs nor does it cover a product subjected to misuse or accidental damage. Warranty repairs are subjected to inspection and evaluation by us.

Liability: We are not liable for damage caused by products that we do not supply or from mishandling in transit, accident, misuse, neglect, lack of care of the product, or service by anyone other than our company.

Contact Us: In case of any kind of dissatisfaction, please Contact us immediately and we promise our utmost support and care until you use our product.