

Mini Converter SDI Distribution 4K



When you need to connect to multiple SDI devices, then Mini Converter SDI Distribution 4K is the perfect solution! Connect a single SDI source to 8 re-clocked SDI outputs with automatic switching between all SD-SDI, HD-SDI, 3G-SDI and 6G-SDI video formats, plus all ASI, ancillary and embedded audio formats.

US\$295

Connections

SDI Video Inputs

Switchable between SD, HD and 6G-SDI.

Reclocking

Yes

SDI Video Outputs

8 outputs automatically match the SDI video input.

Multi Rate Support

Auto detection of SD, HD or 6G-SDI.



Standards

SD Video Standards

525i59.94 NTSC, 625i50 PAL

HD Video Standards

720p50, 720p59.94, 720p60, 1080i50, 1080i59.94, 1080i60, 1080p23.98, 1080PsF23.98, 1080p24, 1080PsF24, 1080p25, 1080PsF25, 1080p29.97, 1080PsF29.97, 1080p30, 1080PsF30, 1080p50, 1080p59.94, 1080p60

2K Video Standards

2K DCI 23.98p, 2K DCI 24p, 2K DCI 25p
2K DCI 23.98PsF, 2K DCI 24PsF, 2K DCI 25PsF

Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30

4K Video Standards

4K DCI 23.98p, 4K DCI 24p, 4K DCI 25p

SDI Compliance

SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE 424M-B, SMPTE 425M, SMPTE ST-2081

SDI Video Rates

SDI video connections are switchable between SD, HD, Ultra HD and DCI 4K.

SDI Video Sampling

4:2:2 and 4:4:4

SDI Audio Sampling

Television standard sample rate of 48 kHz and 24 bit.

SDI Color Precision

4:2:2 and 4:4:4

SDI Color Space

YUV and RGB

SDI Auto Switching

Automatically detects SD, HD or 6G-SDI.

ASI Support

Yes

Power Requirements

Power Supply

+12V universal power supply included with international socket adapters for all countries. Cable tie point.

Power Consumption

4.80 Watts

Operational Voltage Range

12 - 31V DC

Operating Systems



macOS 10.12 Sierra, macOS 10.13 High Sierra or later,



Windows 8.1 or Windows 10.

Physical Specifications



Environmental Specifications

Operating temperature

0° to 40° C (32° to 104° F)

Storage temperature

-20° to 45° C (-4° to 113° F)

Relative Humidity

0% to 90% non-condensing

What's Included

Mini Converter SDI Distribution 4K

12V universal power supply with international socket adapters

Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2018, all rights reserved.
All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.
Local currency conversion may vary.
This website uses remarketing services to advertise on third party websites to previous visitors to our site.
You can opt out at any time by changing cookie settings.

Blackmagic Design Authorized Reseller