PRO173

Fortinge Pro173 is an ideal choice for TV Production,
Obvan and field use since it is developed as a multiple Professional Broadcast LCD Monitor.

It offers a perfect "price – performance" match.
Thanks to its 17.3" panel and 1920x1080 full HD feature, the real video quality can be seen as you catch the right aspect. All functions can be controlled by its adjustable & functional button and keypad.
All activities such as focus assistance, field control. camera

functions, **center sign** etc. can be achieved.

DB-9 interface controls



tally lights that are in 3 colors. Pro173 is served with its standard rackmount kits. As an option it is offered with desktop and field use stand. Vmount battery is especially given for outdoor use.







www.fortinge.com

fb.com/fortingevided

Eğitim Mahallesi Poyraz Sokak Ertogay İş Merkezi, No:3 Kat:2 D:5-6 34722 KADIKÖY / İSTANBUL- TURKEY

+90 (216) 418 11 03



PRO173

SPECIFICATIONS

Screen Size	17.3"
Color Depth	16.7M
Pixe Pitch	0.1989(H)×0.1989(V) mm
Aspect Ratio	16:9
Brightness	400cd/m ²
Contrast Ratio	600:1
Backlight	LED

Input		
1 X BNC	3G-SDI	
1 X HDMI	HDMI	
3 X BNC	YPbPr	
1 X DVI-I	DVI-I	
1 X BNC	Video	
2 X RCA	Audio(L/R)	
The state of the s	·	

Output		
1 X BNC	3G-SDI	
1 X HDMI	HDMI	
3 X BNC	YPbPr	
1 X BNC	Video	
Audio		
Stereo Headphone, Speaker	Audio Out	

General		
Input Voltage	DC9∼24V	
Power Consumption	≤ 26W	
Working Temperature	-10°C∼ 50°C	
Storage Temperature	-20°C∼ 60°C	
Unit Size	426L×285H×35.1D mm (W/O Bracelet)	
Unit Weight	2.75kg (W/O Bracket) / 3.30kg (W/ Bracket)	

SDI Support Format		
480i/576i		
720p(60/59.94/50/30/29/25/24/23.98)		
1080p(60/59.94/50/30/29.97/25/24/24sF/23.98/ 23.98sF)		
HDMI Support Format		
480i/576i/480p/576p		
1080i (60/59.94/50)		
720p (60/59.94/50/30/29/25/24/23.98)		
1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/ 23.98sF)		

Advanced Features

- Peaking Focus Assist(Red highlight over parts of the monochrome image in focus)
- Center Marker
- Screen Marker (80%,85%,90%,93%,96%,2.35:1)
- Image Freeze
- Image Flip (H, V, H/V)
- Camera Mode
- Pixel-to-Pixel
- Check Field (Red, Green, Blue, Mono)
- Built-in LED tally indicators



www.fortinge.com

fb.com/fortingevided

Eğitim Mahallesi Poyraz Sokak Ertogay İş Merkezi, No:3 Kat:2 D:5-6 34722 KADIKÖY / İSTANBUL- TURKEY

+90 (216) 418 11 03

